

## KRY BEARING AFRICA PRIVATE LTD.



QVPN11V200SO Bearing 2D drawings and 3D CAD models

2 Inch | 50.8 Millimeter x 3.14 Inch | 79.756 Millimeter x 2.75 Inch | 69.85 Millimeter QM INDUSTRIES QVPN11V200SO Pillow Block Bearings

Bearing No. QVPN11V200SO

| Category                  | Pillow Block Bearings  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 6.356  |
| EAN                       | 0883450161886  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | V Lock   |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 5/8 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22211  |
| Seals                     | Triple Lip Urethane  |
| Housing Configuration     | 1 Piece Solid  |
| Inch - Metric             | Inch   |
| Other Features            | Double Row   Single Nut  <br>SN Style  |
| Long Description          | 2 Bolt Pillow Block; 2" Bore;<br>2-3/4" Base to Center<br>Height; V Lock Mount;<br>Spherical Roller Bearing; |



## KRY BEARING AFRICA PRIVATE LTD.

|                                  | 6-1/2" Minimum Bolt<br>Spacing; 8.7" Bolt Spacing<br>Maximum; Relubricatable;<br>Cast Ste |
|----------------------------------|---|
| Category                         | Pillow Block  |
| UNSPSC                           | 31171511  |
| Harmonized Tariff Code           | 8483.20.40.80   |
| Noun                             | Bearing   |
| Keyword String                   | Pillow Block  |
| Manufacturer URL                 | http://www.qmbearings.co<br>m   |
| Weight / LBS                     | 14  |
| Bolt Spacing Maximum             | 8.7 Inch   220.98Millimeter   |
| В                                | 2.75 Inch   69.85 Millimeter  |
| Nominal Bolt Center to<br>Center | 7.6 Inch   193 Millimeter   |
| D                                | 3.14 Inch   79.756<br>Millimeter  |
| Bolt Spacing Minimum             | 6.5 Inch   165.1 Millimeter   |
| Actual Bolt Center to<br>Center  | 0 Inch   0Millimeter  |
| d                                | 2 Inch   50.8 Millimeter  |